

AllFive



AllFive 600 mm



**AllFive 600 mm
with opal diffuser**



AllFive 1200 mm



**AllFive 1200 mm
with opal diffuser**



AllFive 1500 mm



**AllFive 1500 mm
with opal diffuser**

Light distribution	100/0	100/0	100/0	100/0	100/0	100/0
Lumen	< 3171	< 2804	< 6448	< 5762	< 8673	< 8339
lm/w	< 160	< 151	< 174	< 155	< 177	< 167
830	●	●	●	●	●	●
840	●	●	●	●	●	●
930	●	●	●	●	●	●
940	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●
Life with standard diodes	L100 50.000 h	L100 50.000 h	L100 50.000 h	L100 50.000 h	L100 50.000 h	L100 50.000 h
Life with premium diodes	L100 100.000 h	L100 100.000 h	L100 100.000 h	L100 100.000 h	L100 100.000 h	L100 100.000 h
On/off	●	●	●	●	●	●
DALI	●	●	●	●	●	●
Organic Response	●	●	●	●	●	●
e-Sense Flex	●	●	●	●	●	●
e-Sense BrightSwitch			●	●	●	●
e-Sense Detect	●	●	●	●	●	●
CLO	●	●	●	●	●	●

Installation accessories Shelter bracket, Wall brackets, Catenary bracket, Wire suspensions

Emergency light On demand